

TWINPLUS MODULE SERIES

HIGH EFFICIENCY MONO-PERC M4-9B-R

370-390W



OUTSTANDING PRODUCT PERFORMANCE


- Competitive high-temperature performance with ameliorated temperature coefficient
- Minimized power loss in cell connection
- Better performance under shading effect
- Decreased nominal operating cell temperature to $45 \pm 2^{\circ}\text{C}$
- Higher power generation with multi-busbar and half-cut technology

TRUSTWORTHY QUALITY AND RELIABILITY

- Guaranteed 0~+5W positive tolerance secures reliable power output
- 5400Pa maximum snow load, 2400Pa maximum wind load
- Optimized electrical design lowers hot spot risk and operating current

PID RESISTANT

- Industry-leading cell processing technology and electrical design ensure solid PID resistance



12-year Product Warranty | 25-year Linear Performance Warranty

MANAGEMENT SYSTEM CERTIFICATES

IEC 61215, IEC 61730

ISO 9001:2015 / Quality management system

ISO 14001:2015 / Standards for environmental management system

ISO 45001:2018 / International standards for occupational health & safety



Bloomberg Tier¹
NEW ENERGY FINANCE



ELECTRICAL TYPICAL VALUES

Model	1000V	PS370M4-20/UH		PS375M4-20/UH		PS380M4-20/UH		PS385M4-20/UH		PS390M4-20/UH	
	1500V	PS370M4H-20/UH		PS375M4H-20/UH		PS380M4H-20/UH		PS385M4H-20/UH		PS390M4H-20/UH	
Testing Condition	STC	NOCT	STC	NOCT	STC	NOCT	STC	NOCT	STC	NOCT	
Rated Power (Pmpp)	370	275	375	279	380	283	385	286	390	290	
Rated Current (Impp)	10.82	8.74	10.89	8.80	10.96	8.86	11.03	8.91	11.10	8.97	
Rated Voltage (Vmpp)	34.20	31.49	34.44	31.71	34.68	31.93	34.91	32.14	35.14	32.35	
Short Circuit Current (Isc)	11.31	9.14	11.40	9.21	11.49	9.28	11.58	9.36	11.69	9.45	
Open Circuit Voltage (Voc)	40.97	38.68	41.18	38.87	41.37	39.05	41.56	39.23	41.74	39.40	
Module Efficiency (%)	20.21		20.48		20.76		21.03		21.30		

STC(Standard Testing Conditions):Irradiance 1000W/m², AM 1.5, Cell Temperature 25°C

NOCT (Nominal Operation Cell Temperature): Irradiance 800W/m², Ambient Temperature 20°C, Spectra at AM1.5, Wind at 1m/S

MECHANICAL CHARACTERISTICS

Cell Type	Monocrystalline 166mm x 83mm
Dimension (L× W × H)	Length: 1762mm (69.37 inch)
	Width: 1039mm (40.91 inch)
	Height: 30mm (1.18 inch)
Weight	20.0kg (44.09 lbs)
Front Glass	3.2mm Toughened Glass
Frame	Anodized Aluminium Alloy
Cable (Including Connector)	4mm ² (IEC), (+):450mm,(-):250mm or Customized Length
Junction Box	IP 68 Rated

TEMPERATURE RATINGS

Voltage Temperature Coefficient	-0.28%/°C
Current Temperature Coefficient	+0.05%/°C
Power Temperature Coefficient	-0.35%/°C
Tolerance	0~+5w
NOCT	45±2°C




ABSOLUTE MAXIMUM RATING

Operating Temperature	From -40 to +85°C
Hail Diameter @ 80km/h	Up to 25mm
Front Side Maximum Static Loading	5400Pa
Rear Side Maximum Static Loading	2400Pa
Maximum Series Fuse Rating	20A
PV Module Classification	II
Fire Rating (IEC 61730)	C
Maximum System Voltage	DC 1500V/1000V

PACKING CONFIGURATION

Container	20' GP	40' HQ
Pieces/Container	336	936

ELECTRICAL CHARACTERISTICS



Note:mm (inch)